# ROLL to ROLL Product Range

## Single & Double Side UV Exposure Roll to Roll

**FPCB / Flex** 



**Photo Chemical** Milling

**Touch Panel** 



**Photovoltaics** 









Arrow



## Solution For High-End Roll to Roll Exposure Processes

Resolution Down to 15µm | 0.6mil

Registration ±5µm | 0.2mil AW/AW

Throughput Up to 9000 images/day **High Savings High Power UV LEDs** 

















#### **AcuReel Specifications**

### **Arrow Specifications**

Applications	FPCB / Flex • P	hoto Chemical Millin	g • Touch Panel •	Photovoltaics	
Web Width	228 to 610 mm   9 to 24"		250 mm   9.85"		
Image Length	Up to 762 mm   up to 30"		Up to 400 mm   up to 15.75"		
Web Thickness	Down to 15μm   Down to 0.6 mil				
Exposure Mode	Simultaneous and independent double side exposure				
Resolution	Down to 15μm   Down to 0.6 mil				
Light Engine	ColliLight™ 2x5kW or 2x8kW	LedLight™	ColliLight™ 1x5kW or	2x5kW LedLight™	
Light Intensity	≥25mW/cm² (5kW lamp)	Up to 55mW/cm <sup>2</sup>	≥25mW/cm² (5kW lan	mp) Up to 55mW/cm²	
	$\geq$ 40mW/cm <sup>2</sup> (8kW lamp) $\geq$ 40mW/cm <sup>2</sup> (8kW lamp)		np)		
Collimation	≤ 1.5°	≤ 1.6°	≤ 1.5°	≤ 1.6°	
Declination	≤ 1°	No declination	≤ 1°	No declination	
Uniformity	> 80%	> 85%	> 80%	> 85%	
Alignment	±5μm Artwork to Artwork		±5μm Artwork to Artwork		
	±8μm Artwork to Web		±8μm Artwork to Web		
CCD cameras	From 4 to 8 CCD cameras				
Throughput	Up to 8000 images per day		Up to 9000 images per day		
Software	17" touch screen with ALTIX SUITE				
Languages	English, Simplified & Traditional Chinese, Korean, German, French				
High Yield					
Air cleanliness	HEPA filter class 100 & Clean Dry Air Network (CDA)				
Construction	Stainless steel				
General Utilities					
Power Supply	220/400/480V 3 Phases 50/60Hz				
Air Supply	6-7 bars – 1.5m³/min				
Power Consumption	17kW (2x5kW lamps) 25kW (2x8kW lamps)		kW lamps)	6kW with LedLight™	
Water Supply	20-30 l/min @3 bars (for 2x5kW) 50-80 l/min @3 bars (for 2x8kW)		rs (for 2x8kW)	20-30 I/min @3 bars	



**UV** source cooling

**Machine Weight** 

**Dimensions** 

Manufacturing, Sales & Service: Europe: Altix France – HQ

Email: central@altix.fr Taiwan: Altix Asia

Email: central@altixasia.com

**Direct Sales & Service:** Asia: Altix China Shanghai, Kunshan, Zhuhai Offices Email: central@altix.cn

4,750kg

5,350mm (L) x 2,978mm (W) x 2,350mm (H)

5,350mm (L) x 2,430mm (W) x 2,350mm (H) (cabins)

North America:

Air cooled / Close Loop Lamp Cooling (CLLC)

Altix NA, Inc. West Coast, Middle West and East Coast

3,700kg

3,190mm (L) x 2,242mm (W) x 2,349mm (H)

Email: central@altix.us





Imaging with us!